RE-LEARN THE POSSIBILITIES OF A MILITARISED COMMERCIAL VEHICLE



PROTECTION IS EVERYTHING



In today's ever changing world, tactical vehicles need the modularity to fulfil a variety of roles in order to offer the most cost effective capability. The Fox Rapid Reaction Vehicle (RRV-x) has been designed with enhanced weight carrying capacity, internal CH-47 air transportability and increased off-road agility to push the boundaries of payload, mobility and performance.

T +44 (0)1932 857766

F+44 (0)1932 855694

■ info@jankel.com

w www.jankel.com

DIMENSION AND WEIGHTS

- Length: 5,285mm • Width: 1,870mm • Height: 1,870mm
- Kerb mass: 2,600kg (standard configuration)
- Payload: 1,800kg+

AIR TRANSPORTABILTY

- C130 tie-downs
- CH47 internal dimensions
- CH47 under-slung (optional)

ENGINE AND DRIVETRAIN

- 2.8 litre 4 cylinder diesel with turbo charger
- Bespoke Heavy Duty wheels
- Transmission 6 speed automatic
- Heavy Duty Oil Cooler

- Transfer case, 2-speed 4wd
- Power 225HP with 525 Nm torque
- Tyres: 245/75 R17 all terrain
- Axle Differentials Lockable (Front and Rear)

SEATING AND BODY VARIANTS

- Left hand/right hand drive positions
- 2 front + 3 intermediate + cargo bed (Patrol Variant)
- 2 front + 2 intermediate + cargo bed (Patrol Variant)
- 2 front + 3 intermediate + 4 rear (Troop Carrier Variant)

PERFORMACE

- Max speed: 120kpm
- · Wading: 700mm
- Fuel capacity: 140 litres
- Departure angle: 29° Configuration Dependent
- Step climb: 300mm

- Ground clearance 279mm
- Fuels: diesel (petrol optional)
- Approach angle: 41º
- Breakover angle 154°
- Range: (typical) 1500km

EQUIPMENT OPTIONS (EXAMPLES)

- Winch: front, rear, cargo-loading
- Smoke dischargers
- Digital instrument panel
- Front rock-strike protection plate
- Electrical system: 12v/24v DC
- Lower rear suspension system
- Infa-Red lighting
- Pull-out laptop compartment
- Under-belly protection plate
- Personal weapon stowage
- Automatic transmission
- Communication suite
- Modular dash panel
- Modular armour solution (optional)
- Front: post and cradle mounts for 7.62mm GPMG or 5.56mm
- Main: 1,050mm ring (850mm ring optional) and soft-mounts for 0.50 cal, 40mm AGL, 7.62mm GPM or 5.56mm



To find out more about the **FOX RRV-x please contact:**

T+44(0)1932857766

E info@jankel.com

